Table 1. Changes to Rel B RBR Class - RTM baseline 01-25-97

RBR_id	req_key	req_category	segment	req_type	s_verif_method	s_verif_stat	a_verif_method	a_verif_stat	CCR	text	interpretation text	clarification
EOSD0545#B	7100	mission fulfillment	FOS | SDPS | CSMS	functional	analysis	un-verified	analysis	un-verified	96-0956A	ECS shall be able to accommodate growth (e.g., capacity) in all of its functions as well as the addition of new functions.	~~For compliance refer to Segment Specification 305/DV2, System Design Spec (SDS) 207/SE1~~.	
EOSD1015#B	6506	mission critical	SDPS	performance	demo	un-verified	demo	un-verified		The DADS at each DAAC that receives instrument level 0 data from EDOS shall provide the capability to ingest and archive the data at a rate that is equivalent to 1.2 times the DAAC average level 0 input rate.	ECS interprets "archive" in this requirement to mean the capture of L0 data from EDOS in safe storage.	
EOSD2640#B	8915	mission essential	SDPS | CSMS	security	test	un-verified	test	un-verified	96-1468A	ECS elements shall relinquish a connection between the element and a user when the user has not been active for a configurable period of time.		"relinquish a connection" mean suspend the session